B.E.G. LUXOMAT®

DATA SHEET

Ceiling mounted occupancy detectors - Slave devices

PD4-S



white mat, similar to white mat, similar to white mat, similar to RAL9010 , Part No. 92142 RAL9010 , Part No. 92163 RAL9010 , Part No. 92254

Product Information

- Slave device detector with extended detection area
- For extending the detection area of a Master device
- Trigger pulse to master device upon detected movement independent of the ambient light level
- Compatible with 230 V devices. Concerning exceptions please see the respective master device.
- Typical applications: monitoring of large areas like underground garages, gyms, warehouses, loading ramps, halls

Technical Data

Voltage:	110 – 240 V AC 50 / 60 Hz		
Dimensions:	SM= Ø 101 x 76 mm FM= Ø 97 x 84 mm FC= Ø 97 x 103 mm		
Power consumption:	approx. 0.2 W		
Detection area:	vertical 360°		
Range:	max. Ø 24 m across max. Ø 8 m towards max. Ø 6.4 m seated		
Monitored area (tangential movement):	450 m² / 2.5 m mounting height		
Mounting height	2 m / 10 m / 2.5 m		

min./max./recommended:


Degree / class of protection:	SM= IP54 / Class II FM= IP20 / Class II FC= IP20 / Class II
Ambient temperature:	-25 °C to +50 °C
Housing:	Polycarbonate, UV-resistant
Pulse interval:	2 or 9 sec

Description

Description	Colour	Part number	EAN number
PD4-S-SM	white mat, similar to RAL9010	92142	4007529921423
PD4-S-FM	white mat, similar to RAL9010	92163	4007529921638
PD4-S-FC	white mat, similar to RAL9010	92254	4007529922543


Accessory


Description	Colour	Part number	EAN number
Wire basket BSK (Ø 200 x 90 mm)	white	92199	4007529921997
Surface mounting socket (IP65) PD4-SM IP54	white	92376	4007529923762




Dimensions 92254

Dimensions 92163








Dimensions 92142

Range diagram

- 1: Walking across
- 2: Walking towards
- 3: Seated activity



Wiring diagram

© 2020 B.E.G. Brück Electronic GmbH